



ARMSTRONG ULTIMA⁺

Armstrong ULTIMA⁺ not only offers a finely textured and durable surface with a brighter “blue-white” colour and high light reflectance, it also offers a balance of both sound absorption and sound attenuation as well as being C2C Bronze certified.

Key features

- Good sound absorption: up to 0.75(H) α_w
- Very high light reflectance: 87%
- Reinforced scratch resistant face
- Better finish and more durable edges
- C2C Bronze certified / ISO 5 / A+
- 30 year system guarantee
- Available with SL2 MicroLook 90 edge detail





Application areas

Ideal for meeting rooms or waiting areas
Armstrong ULTIMA⁺ Planks: ideal for both open areas and corridors.

OFFICE
Takeda, Warsaw (PL)
Armstrong ULTIMA⁺ Vector



ARMSTRONG ULTIMA⁺

EDGE DETAIL	BOARD	TEGULAR	MICROLOOK 90	VECTOR	FINESSE	SL2
						
THICKNESS (mm)	19	19	19	19	19	19
MODULE (mm)	600 x 600 7661M 675 x 675 7662M 1200 x 600 7663M	600 x 600 7664M 675 x 675 7665M 1200 x 600 7666M	600 x 550 7713M 600 x 600 7674M 675 x 675 7675M 1200 x 300 7676M 1200 x 600 7677M 1500 x 600 7703M	600 x 600 7681M	600 x 600 7715M 1200 x 600 7716M	1500 x 300 7699M 1720 x 300 7700M 1800 x 300 7701M 2500 x 300 7702M
SUSPENSION SYSTEMS	Prelude 24 XL ² /TL ² Prelude 24 Sixty ² XL ² /TL ²	Prelude 24 XL ² /TL ² Prelude 24 Sixty ² XL ² /TL ²	Prelude 15 TL/XL ² Interlude HRC XL ² Silhouette 6mm XL ²	Prelude 24 XL ² /TL ² Prelude 24 Sixty ² XL ² /TL ²	System Z - L-Bar	System Z - T-Bar System Z - Z-Bar System Z Corridor - T-Bar System Z Corridor - Z-Bar

COLOURS



Global White

SUSTAINABILITY



33-37¹



A+²



E1



IBU

¹ Depends on thickness, edge detail and size of tile.

² Except Vector: A

ACOUSTICS



EN ISO 10848-2
& EN ISO 717-1



EN ISO 140-3
& EN ISO 717-1



EN ISO 354
& EN ISO 11654

Hz α_p

	D _{ntw}	R _w	α_w	Class	NRC	125	250	500	1000	2000	4000
Board, Tegular, MicroLook 90	36 dB	18 dB	0.70(H)	C	0.75	0.40	0.50	0.65	0.85	0.95	1.00
Vector	33 dB	-	0.75(H)	C	0.75	0.35	0.55	0.65	0.80	0.95	0.90
Finesse	39 dB	-	0.70(H)	C	0.75	0.40	0.50	0.65	0.85	0.95	1.00
SL2	40 dB	-	0.65(H)	C	0.65	0.35	0.45	0.55	0.75	0.90	1.00

FIRE REACTION



EEA Euroclass A2-s1, d0
EN 13501-1

RUS KM1 (G1, V1, D1, T1)
FZ 123

OTHER PERFORMANCES & FEATURES



87%



$\lambda = 0.052$ W/m K

EN 12667
& ISO 8301



95% RH



5.0 kg/m²
(Board, Tegular,
MicroLook 90, Finesse)
5.6 kg/m²
(SL2)
5.8 kg/m²
(Vector)



ISO 14644-1



CUSTOM OPTIONS



Dimensions