



COLORTONE RANGE

COLORTONE offers a simple way to play with colours in ceilings, available in DUNE eVo or NEEVA surfaces to suit your acoustic requirements.

Key features

- 3 edge details available (DUNE eVo)
- Excellent acoustical absorption:
1.00 α_w (NEEVA)

Application areas

Ideal for cafeterias, cinemas, theatres.

LEISURE - Uttoxeter Cinema (UK)
COLORTONE NEEVA Black



Inspiring Great Spaces®

Armstrong®
CEILING SOLUTIONS

COLORTONE NEEVA

EDGE DETAIL	BOARD																																		
																																			
THICKNESS (mm)	15																																		
MODULES (mm)	600 x 6002695DBK2695DCG2695DNY2695DMT 1200 x 6002696MBK2696MCG2696MNY2696MMT																																		
SUSPENSION SYSTEMS	Prelude 24 XL ² / TLS Prelupe 24 CR / TLS Prelude 24 Sixty ² XL ² / TLS																																		
COLOURS	 Black (BK)Cement (CG)Navy (NY)Metal (MT)																																		
SUSTAINABILITY	 20A E1																																		
ACOUSTICS	 EN 20140-9 & EN ISO 717-1EN ISO 140-3 & EN ISO 717-1EN ISO 354 & EN ISO 11654 <table><tr><th></th><th>D_{ncw}</th><th>R_w</th><th>α_w</th><th>Class</th><th>NRC</th><th>125</th><th>250</th><th>500</th><th>1000</th><th>2000</th><th>4000</th></tr><tr><td>Board 15 mm</td><td>-</td><td>7 dB</td><td>1.00</td><td>A</td><td>0.95</td><td>0.40</td><td>0.90</td><td>1.00</td><td>0.90</td><td>1.00</td><td>1.00</td></tr></table>												D_{ncw}	R_w	α_w	Class	NRC	125	250	500	1000	2000	4000	Board 15 mm	-	7 dB	1.00	A	0.95	0.40	0.90	1.00	0.90	1.00	1.00
	D_{ncw}	R_w	α_w	Class	NRC	125	250	500	1000	2000	4000																								
Board 15 mm	-	7 dB	1.00	A	0.95	0.40	0.90	1.00	0.90	1.00	1.00																								
FIRE REACTION	<table><tr><td>EEA</td><td>Euroclass A1 (Black, Navy)</td><td>RUS</td><td>KM1 (G1, V1, D1, T1)</td></tr><tr><td></td><td>Euroclass A2-s1,d0 (Cement)</td><td></td><td></td></tr><tr><td></td><td>Euroclass A2-s2,d0 (Metal)</td><td></td><td></td></tr></table> EN 13501-1FZ 123											EEA	Euroclass A1 (Black, Navy)	RUS	KM1 (G1, V1, D1, T1)		Euroclass A2-s1,d0 (Cement)				Euroclass A2-s2,d0 (Metal)														
EEA	Euroclass A1 (Black, Navy)	RUS	KM1 (G1, V1, D1, T1)																																
	Euroclass A2-s1,d0 (Cement)																																		
	Euroclass A2-s2,d0 (Metal)																																		
OTHER PERFORMANCES & FEATURES	 $\lambda = 0.033 \text{ W/m K}$  95% RH  1.2 kg/m²  30YEAR system guarantee 																																		
CUSTOM OPTIONS	 Colours¹Dimensions ¹ Prelude suspension systems are available in following standard colours: Black (BK), Silver Grey RAL9006 (SG), Brass (BS), Chrome (CE), White RAL9010 (WR). A choice of over 180 RAL colours is available as a special order.																																		

COLORTONE FINE FISSURED

EDGE DETAIL	BOARD																																											
																																												
THICKNESS (mm)	15																																											
MODULES (mm)	600 x 600 9121MBK																																											
SUSPENSION SYSTEMS	Prelude 24 XL ² / TLS Prelude 24 CR / TLS Prelude 24 Sixty ² XL ² / TLS																																											
COLOURS	 Black (BK)																																											
SUSTAINABILITY	 51   A  E1																																											
ACOUSTICS	 EN ISO 10848-2 & EN ISO 717-1  EN ISO 354 & EN ISO 11654 <table><tr><th></th><th colspan="10">Hz α_p</th></tr><tr><th></th><th>D_{nfw}</th><th>α_w</th><th>Class</th><th>NRC</th><th>125</th><th>250</th><th>500</th><th>1000</th><th>2000</th><th>4000</th></tr><tr><td>Board 15 mm</td><td>36 dB</td><td>0.60 (H)</td><td>C</td><td>0.60</td><td>0.40</td><td>0.40</td><td>0.55</td><td>0.75</td><td>0.75</td><td>0.75</td></tr></table>												Hz α_p											D _{nfw}	α_w	Class	NRC	125	250	500	1000	2000	4000	Board 15 mm	36 dB	0.60 (H)	C	0.60	0.40	0.40	0.55	0.75	0.75	0.75
	Hz α_p																																											
	D _{nfw}	α_w	Class	NRC	125	250	500	1000	2000	4000																																		
Board 15 mm	36 dB	0.60 (H)	C	0.60	0.40	0.40	0.55	0.75	0.75	0.75																																		
FIRE REACTION	 EEA Euroclass A2-s1, d0 EN 13501-1 RUS KM1 (G1, V1, D1, T1) FZ 123																																											
OTHER PERFORMANCES & FEATURES	 EN 12667 & ISO 8301 $\lambda = 0.060 \text{ W/m K}$  95% RH  3.4 kg/m²  30YEAR system guarantee BIM READY																																											
CUSTOM OPTIONS	 Colours¹ ¹ Prelude suspension systems are available in following standard colours: Black (BK), Silver Grey RAL9006 (SG), Brass (BS), Chrome (CE), White RAL9010 (WR). A choice of over 180 RAL colours is available as a special order.																																											

All dimensions in millimeters. All sizes are nominal. Product availability may vary. Please contact us or visit www.armstrongceilings.co.uk for more information.