



ATENA S.P.A. HAS A QUALITY
MANAGEMENT SYSTEM
CERTIFICATED BY RINA
IN COMPLIANCE WITH ISO 9001



Steel Strong Easy T24 Overlap

Patent number: VE2002U000027

PRODUCT TYPE

Visible T-grid system base 24 mm (nominal)

CLIP MATERIAL

Stainless steel 0,4 mm thickness

STRUCTURE MATERIAL

Main profile: galvanised steel DX51D-Z100 thick. 0,35 mm
Cross T: galvanised steel DX51D-Z100 thick. 0,30 mm

CAPPING MATERIAL

pre-painted steel thick. 0,30 mm

T-GRID CONNECTION

Main profile: head to head connection with printed clip
Cross profiles: stainless steel clip

COLOURS AND PERFORMANCE

White Black Silver	corrosion resist. C2
Totally white	corrosion resist. C3
RAL/NCS coating	corrosion resist. C2 C4
Antibacterial treatment	corrosion resist. C2 C4

T-GRID WEIGHT

1,074 kg/mq (3700 - 1200 - 600 h38)
0,97 kg/mq (3700 h38 | 1200 - 600 h32)
hanger and wall angles not included

PACKAGING

Light brown boxes with red strip




VIEW

T-grid profiles


STANDARD

OVERLAP



SPECIAL

OVERLAP



TECHNICAL PERFORMANCES

	EXPOSURE CLASS	A Class	
	CLIP TENSILE STRENGTH	180 N	
	FLEXION RESISTANCE	Maximum span mm 1200 - 1 Class EN13964	
	CORROSION RESISTANCE	Galvanized steel products: C2 Class Pre-painted galvanized steel products: C3 Class Post-painted galvanized steel products: C4 Class Pre/post-painted aluminium products: C5 Class	
	(RH%) RELATIVE HUMIDITY RESISTANCE	Galvanized steel products: ≤ 90% Pre/post-painted galvanized steel products: > 90% Stainless steel and aluminium products: > 90	
	FIRE REACTION UNI EN 13501-1	A1 Class	
	FIRE RESISTANCE UNI EN 13501-2	REI 120 rockwool panels 75mm thick. REI 120 rockwool panels 15mm thick. REI 120 mineral fiber panels 15mm thick. 75 minutes mineral fiber panels 14mm thick.	Concrete deck UNI EN 13501-1-2 Pedralles deck UNI EN 13501-1-2 Mild steel profile S275 BS476:Part.21:1987
	METAL CEILING MAXIMUM LOAD	12 kg/m ²	
	LIGHT REFLECTION	Gloss smooth white: up to 85% ISO 7724-2 (3)	
	COLOR STABILITY	In compliance with standard technical tolerances. Test according to the ΔE - CIELab method. ISO 7724-2 (3)	
	CLEANING	Wet cloth with warm water and neutral non-abrasive detergents.	
	DURABILITY OF PAINTED ITEMS	C Class EN13964	
	DURABILITY OF GALVANIZED ITEMS	B Class EN13964	


SUSTAINABILITY

	RELEASE OF DANGEROUS SUBSTANCES*	None CAM 2.4.13 EN13964		FORMALDEHYDE* E1 Class CAM 2.3.5.5
	DISASSEMBLY*	Steel Aluminium 100% recyclable CAM 2.4.11		MATERIAL DEMOLITION AND REMOVAL* Non hazardous waste in compliance with CAM 2.5.1.
	RECYCLED PRODUCT CONTENT*	CAM 2.4.1.8 compliance		GREEN BUILDING Requirements: LEED (BREEAM and ITACA for cross-section aspects)


* Data declaration as required by the ISO 14021 standard

EASY T24 OVERLAP


Main profile 3700 mm




Main T clip




Cross profile 1200 mm



Easy Hook




Cross profile 600 mm



DIMENSIONS

CODE	LENGHT	DIMENSION	PCS/BOX	BOX WEIGHT	BOX/PALLET	PALLET WEIGHT
RY124370BRTAR	3700 mm	24x38 mm	24	31,19 kg	36	1123 kg
RY124120BRTAR	1200 mm	24x32 mm	50	16,66 kg	60	1000 kg
RZ124120BTRRH	1200 mm	24x38 mm	50	18,08 kg	60	1085 kg
RY124060BRTAR	600 mm	24x32 mm	75	12,20 kg	96	1171,2 kg
RZ124060BTRRH	600 mm	24x38 mm	50	9,04 kg	120	1085 kg

* The grey part of code changes according to the features of the required.



INCIDENCES

B24 lenght	3700 mm	1200 mm	600 mm
module 600x600 mm	0,85 ml/mq	1,70 ml/mq	0,85 ml/mq
module 600x1200 mm	0,85 ml/mq	1,70 ml/mq	-


BEARING CAPACITY

Maximum load = 12 kg/mq | Maximum deflection = L/360
Lab. Test Cert TV


For different deflection, consider this following table

MAX FLEXION	L/300	L/360	L/400	L/500
MULTIPLYER VALUE	1,2	1	0,9	0,72

(1) Main T 3700 mm
(2) Cross T 1200 mm
(3) Cross T 600 mm




INSTALLATION STEPS



***Nota:** verify interaxes and hanger models according to the load at m² the antiseismic report and particular conditions.
The fastening must be checked with regard to the loads, the anchoring base features and the installation accuracy, in order not to compromise the stability of the metal ceiling system. Lightings, accessories and systems must not weigh on the metal ceiling system, but must be independently suspended.

- 1 Draw the lines of the perimeter frame. Determine the height of the ceiling with a level and mark it with a string. Proceed with the installation of structure.
- 2 Install the wall angles with nails, screws and / or plugs suitable to the wall material.
- 3 Fix the hangers to the anchoring base; hook the 3700 mm "main profiles" on the hangers with an distance of 800 | 900 mm*.
- 4 Complete the installation of man profiles at a distance of 1200 mm.
- 5 Insert the clips* of 1200 mm cross T on the main T punches.
- 6 Insert the clips* of 600 mm cross T on the 1200 mm cross T punches.

HANGERS



***Nota:** to set up a proper coupling of the structure, hold the left side of the punched profile and press slightly to snap the clip into place. The click ensures the proper attachment of the structure.
To release, press the tab of the locking clip and remove the profile..

CLEANING, MAINTENANCE AND REMOVAL INSTRUCTIONS

Cleaning and maintenance require some attention and care even though are easy to make and don't take much time. It is necessary to use warm water and neutral and non-abrasive detergents. Metal ceilings maintenance usually refers to: placement, alignment or replacement of damaged or broken modules (panels, staves, baffles, open cells) which can be also removed for restoration or maintenance of the system below.

In order to ensure an excellent results, the maintenance work must be carried out by specialised workers trained with technical data sheets about setting, removal and maintenance of the metal ceilings. Using inadequate tools can damage the bearing structure, causing adherence loss or even accidental modules fall. All the maintenance intervention must follow the technical data sheet instructions or specific information when provided and every diversity has to be promptly reported. Each worker charged with maintenance operation must carefully remove the modules, perform the intervention and do not alter the metal ceiling structure, the hanging system and the connection between these elements.

When the maintenance is over, modules must be installed again, checking that these are well hooked or positioned if they are lay-in/on on a visible structure and that the flatness of the assembly is guaranteed. Any difference in level is caused by wrong installation and, for this reason, the system must be quickly controlled.

STORAGE MODE

Materials supplied by Atena S.p.A. shall be maintained in good condition from purchase to installation. Materials must be stored in a closed, clean and dry site, not under direct light. Atena S.p.A. protects its products with resistant packaging under normal handling. Please handle packages with care to avoid shocks and inappropriate handling that might damage what is provided. The manual handling must be carried out with caution and in compliance with safety regulations at work. For carriage of packaged products on pallets, provide a mechanical transport to avoid damages or risks resulting from inadequate transport.

SUSTAINABILITY AND SAFETY

All Atena metal ceilings are made with products that do not release dangerous substances into the environment including formaldehyde. Coating and / or sublimation are free from Volatile Organic Compounds (VOC). The products will be recyclable and as a whole manufactured using recycling processes materials, the recycled material percentage is calculated for each type of product, in compliance with CAM requirements and declared according to the ISO 14021 standard. The metal ceiling systems contribute to getting credits for the certification of building design, construction and sustainable and efficient management according to the LEED protocol and to the BREEAM and ITACA cross-cutting aspects.

FASTENERS

Atena supplies the hangers and accessories such as screws, washers and nuts to connect the elements of its own supply only. Lightings, accessories and systems must not weigh on the metal ceiling system, but must be independently suspended. The fastening must be checked with regard to the loads, the anchoring base features and the installation accuracy, in order not to compromise the stability of the metal ceiling system.

NORMATIVE REQUIREMENTS

Atena S.p.A. has adopted a quality management system in compliance with the UNI EN ISO 9001 standard.

All Atena metal ceilings are produced for indoor applications, in compliance with Technical Standards for Construction NTC 2018 and relative circular requirements, the Minimum Environmental Criteria CAM (Ministerial Decree 11 October 2017), the specific technical standards applicable UNI EN 13964 and 14195. Each Atena S.p.A. product has its own DOP (CE Declaration of Performance) according to the European Law for construction products 305/2011.

The performance properties declared in D.o.P. Declarations of Performance provided by Atena S.p.A. are guarantees, if the metal ceiling is installed in the environment conditions for which it has been conceived and the recommended maintenance is executed.

Precisely, metal ceilings are non-structural construction elements therefore they must be properly sized in order to withstand with adequate safety against all actions that can stress the building, such as, but not limited to, earthquakes, winds, thermal expansion, humidity, etc., in relation to the installation site, the building use and the project technical features. Check with Atena technical department the specific environmental conditions to which the product will be subjected, in order to choose the most suitable materials for the installation site.

In the case of outdoor installation, the metal ceilings are not covered by an harmonized technical standard, therefore they are not subject to the regulation 305/2011. They are in any case subjected to the NTC 2018 and to the safety checks of civil constructions, and must be properly sized according to the installation site environmental conditions, to the structural features and to the project specifications.

Independently by information, suggestions, advices and technical opinions exchanged between the parts, during pre-agreement negotiations Atena S.p.A. will manufacture the products only according to the orders received and the technical drawings/projects attached, having no responsibility on what is not indicated in the order, in the technical drawings or in the project.

All rights are reserved and subject to industrial protection. Changes to the illustrated products, even if partial, can be carried out only if explicitly authorized by the company Atena S.p.A. All data provided and illustrated are indicative and Atena S.p.A. reserves the right to make changes at any time according the business needs and the production processes.

The information contained in this following sheet must to be considered updated at the date of writing. Changes in product performance occurred after that date may affect the accuracy of the data sheet: it is compulsory for users to make sure to have the latest version of this sheet.

WARRANTY

Atena S.p.A. as a manufacturer, covers the manufacturing defects of its products; Except as provided in the specific warranty extensions, the warranty period is one year from delivery of goods. Any complaints must be communicated in accordance with the sales terms and conditions.

The Atena metal ceilings system components have been conceived for this purpose only, any other use is considered improper.