




AMF ECOMIN Orbit

- ECOMIN Orbit is a value-for-money product with a structured and ground surface
- Good light reflectance (85%)
- Ideal for retail environments



Edge details Additional edge details on request		Board 														
Thickness (mm)		13														
Dimensions (mm) Additional sizes on request		600 x 600 1200 x 600														
System		Exposed demountable - System C Exposed - Bandraستر, demountable - System I.3 Exposed - Corridor, demountable - System F.3														
Weight		2.8 - 3.3 kg / m²														
Colour		White														
Sound absorption		EN ISO 354 $\alpha_w = \mathbf{0.20 (L)}$ as per EN ISO 11654 - Class E <table><tr><th>Frequency f (Hz)</th><th>125</th><th>250</th><th>500</th><th>1000</th><th>2000</th><th>4000</th></tr><tr><td>α_p Board</td><td>0.40</td><td>0.30</td><td>0.15</td><td>0.15</td><td>0.20</td><td>0.20</td></tr></table> NRC = 0.20 as per ASTM C 423	Frequency f (Hz)	125	250	500	1000	2000	4000	α_p Board	0.40	0.30	0.15	0.15	0.20	0.20
Frequency f (Hz)	125	250	500	1000	2000	4000										
α_p Board	0.40	0.30	0.15	0.15	0.20	0.20										
Fire reaction		Euroclass A2-s1, d0 as per EN 13501-1 RUS KM1 (G1, V1, D1, T1) as per FZ 123														
Light reflectance		85%														
Thermal conductivity		$\lambda = \mathbf{0.060 W/m K}$ as per EN 12667														
Humidity resistance		70% RH														
Indoor air quality		 A+  E1														
Cleanability	 															
Sustainability		31-44%														

Products may vary from country to country.
Please contact your local sales representative.
For further information and legal notice, please visit our website.